

SAFETY DATA SHEET ANTIQUAX MIRROR & GLASS CLEANER

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

Revision date: 23/03/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ANTIQUAX MIRROR & GLASS CLEANER

Product number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Glass cleaner.

Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier Rustins Ltd

Waterloo Road

London NW2 7TX United Kingdom +44 (0)20 8450 4666 rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)20 8450 4666 (Office hours only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

ANTIQUAX MIRROR & GLASS CLEANER

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Contains Propan-2-ol

Detergent labelling 5 - < 15% aliphatic hydrocarbons, < 5% perfumes

Supplementary precautionary

P264 Wash contaminated skin thoroughly after handling.

statements P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Propan-2-ol 30- < 60%

FC number: 200-661-7 CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

Petroleum gases, liquefied 5 - <10%

CAS number: 68476-85-7 EC number: 270-704-2

Classification

Flam. Gas 1A - H220 Press. Gas (Liq.) - H280

1 - <5% 2-butoxyethanol

CAS number: 111-76-2 EC number: 203-905-0

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

ANTIQUAX MIRROR & GLASS CLEANER

1-methoxypropan-2-ol 1 - <5%

CAS number: 107-98-2 EC number: 203-539-1

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

Diethyl phthalate <1%

CAS number: 84-66-2 EC number: 201-550-6

Classification
Not Classified

Turpentine, oil <1%

Classification

Flam. Liq. 2 - H225

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Skin Sens. 1 - H317

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and

ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Due to the

small packaging, the risk of ingestion is minimal. Do not induce vomiting unless under the

direction of medical personnel.

Skin contact Remove contamination with soap and water or recognised skin cleansing agent.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical

attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

ANTIQUAX MIRROR & GLASS CLEANER

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact Vapour or spray in the eyes may cause irritation and smarting. Particles in the eyes may

cause irritation and smarting.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

> Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and

propellant. Vapours may form explosive mixtures with air.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be

> taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised

contents and propellant. Take precautionary measures against static discharges.

6.2. Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Not considered to be a **Environmental precautions**

significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

ANTIQUAX MIRROR & GLASS CLEANER

Methods for cleaning up

Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Provide adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. The product is flammable. Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Do not expose to temperatures exceeding 50°C/122°F. Avoid inhalation of vapours and spray/mists. Avoid contact with eyes.

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Wash contaminated skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep away from oxidising materials, heat and flames. Store in a cool and well-ventilated place. Protect from sunlight. Keep containers upright. Protect containers from damage. Do not expose to temperatures exceeding 50°C/122°F. Do not store near heat sources or expose to high temperatures. Store in accordance with national regulations.

Storage class

Chemical storage. Aerosol containers and lighters

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Petroleum gases, liquefied

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

2-butoxyethanol

ANTIQUAX MIRROR & GLASS CLEANER

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³ Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³ SL

1-methoxypropan-2-ol

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³ Sk

Diethyl phthalate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ Short-term exposure limit (15-minute): WEL 10 mg/m³

Turpentine, oil

Long-term exposure limit (8-hour TWA): WEL 100 ppm 566 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 850 mg/m³

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin.

Propan-2-ol (CAS: 67-63-0)

DNEL Workers - Inhalation; Long term systemic effects: 500 mg/m³

Workers - Dermal; Long term systemic effects: 888 mg/kg/day

General population - Inhalation; Long term systemic effects: 89 mg/m³ General population - Dermal; Long term systemic effects: 319 mg/kg/day General population - Oral; Long term systemic effects: 26 mg/kg/day

PNEC - Fresh water; 140.9 mg/l

- marine water; 140.9 mg/l

- STP; 2251 mg/l

Sediment (Freshwater); 552 mg/kgSediment (Marinewater); 552 mg/kg

Soil; 28 mg/kgOral; 160 mg/kg

2-butoxyethanol (CAS: 111-76-2)

DNEL Workers - Inhalation; Long term systemic effects: 98 mg/m³

Workers - Inhalation; Short term systemic effects: 1091 mg/m³ Workers - Inhalation; Short term local effects: 246 mg/m³ Workers - Dermal; Long term systemic effects: 125 mg/kg/day Workers - Dermal; Short term systemic effects: 89 mg/kg/day

General population - Inhalation; Long term systemic effects: 59 mg/m³ General population - Inhalation; Short term systemic effects: 426 mg/m³ General population - Inhalation; Short term local effects: 147 mg/m³ General population - Dermal; Long term systemic effects: 75 mg/kg/day General population - Oral; Long term systemic effects: 89 mg/kg/day General population - Oral; Long term systemic effects: 6.3 mg/kg/day General population - Oral; Short term systemic effects: 26.7 mg/kg/day

PNEC - Fresh water; 8.8 mg/l

- marine water; 0.88 mg/l

- STP; 463 mg/l

Sediment (Freshwater); 34.6 mg/kgSediment (Marinewater); 3.46 mg/kg

Soil; 2.33 mg/kgOral; 20 mg/kg

ANTIQUAX MIRROR & GLASS CLEANER

1-methoxypropan-2-ol (CAS: 107-98-2)

DNEL Workers - Inhalation; Long term systemic effects: 369 mg/m³

> Workers - Inhalation; Long term systemic effects: 553.5 mg/m3 Workers - Inhalation; Short term local effects: 553.5 mg/m³ Workers - Dermal; Long term systemic effects: 183 mg/kg/day

General population - Inhalation; Long term systemic effects: 43.9 mg/m³ General population - Dermal; Long term systemic effects: 78 mg/kg/day General population - Oral; Long term systemic effects: 33 mg/kg/day

PNEC - Fresh water; 10 mg/l

- marine water; 1 mg/l

- Intermittent release; 100 mg/l

- STP; 100 mg/l

- Sediment (Freshwater); 52.3 mg/kg - Sediment (Marinewater); 5.2 mg/kg

- Soil; 4.59 mg/kg

Ammonia (CAS: 1336-21-6)

DNEL Workers - Inhalation; Long term systemic effects: 47.6 mg/m³

> Workers - Inhalation; Short term systemic effects: 47.6 mg/m³ Workers - Inhalation; Long term local effects: 14 mg/m³ Workers - Inhalation; Short term local effects: 36 mg/m³

Workers - Dermal; Long term systemic effects: 6.8 mg/kg/day

Workers - Dermal; Short term systemic effects: 6.8 mg/kg/day

General population - Inhalation; Long term systemic effects: 23.8 mg/m3 General population - Inhalation; Short term systemic effects: 23.8 mg/m³ General population - Inhalation; Long term local effects: 2.8 mg/m³ General population - Inhalation; Short term local effects: 7.2 mg/m³ General population - Dermal; Long term systemic effects: 68 mg/kg/day General population - Dermal; Short term systemic effects: 68 mg/kg/day

PNEC - Fresh water; 0.001 mg/l

- marine water; 0.001 mg/l

2,2',2"-nitrilotriethanol (CAS: 102-71-6)

DNEL Workers - Inhalation; Long term systemic effects: 5 mg/m³

Workers - Inhalation; Long term local effects: 5 mg/m³

Workers - Dermal; Long term systemic effects: 6.3 mg/kg/day

General population - Inhalation; Long term systemic effects: 1.25 mg/m3 General population - Inhalation; Long term local effects: 1.25 mg/m³ General population - Dermal; Long term systemic effects: 3.1 mg/kg/day General population - Oral; Long term systemic effects: 13 mg/kg/day

PNEC - Fresh water; 0.32 mg/l

- marine water; 0.032 mg/l

- STP; 10 mg/l

- Sediment (Freshwater); 1.7 mg/kg - Sediment (Marinewater); 0.17 mg/kg

- Soil; 0.151 mg/kg

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran (CAS: 1222-05-5)

ANTIQUAX MIRROR & GLASS CLEANER

DNEL Workers - Inhalation; Long term systemic effects: 22 mg/m³

Workers - Dermal; Long term systemic effects: 60 mg/kg/day

General population - Inhalation; Long term systemic effects: 6.5 mg/m³ General population - Dermal; Long term systemic effects: 36 mg/kg/day General population - Oral; Long term systemic effects: 3.8 mg/kg/day

PNEC - Fresh water; 4.4 μ g/l

- marine water; 0.44 µg/l

- STP; 1 mg/l

Sediment (Freshwater); 2 mg/kgSediment (Marinewater); 0.394 mg/kg

Soil; 0.31 mg/kgOral; 3.3 mg/kg

Reaction mass of 2-methylbutyl salicylate and pentyl salicylate

DNEL Workers - Inhalation; Long term systemic effects: 3.17 mg/m³

Workers - Dermal; Long term systemic effects: 0.9 mg/kg/day

General population - Inhalation; Long term systemic effects: 0.78 mg/m³ General population - Dermal; Long term systemic effects: 0.45 mg/kg/day General population - Oral; Long term systemic effects: 0.45 mg/kg/day

PNEC - Fresh water; 0.77 μg/l

marine water; 0.077 μg/l
Intermittent release; 7.7 μg/l

- STP; 10 mg/l

Sediment (Freshwater); 0.389 mg/kgSediment (Marinewater); 0.039 mg/kg

Soil; 1.786 mg/kgOral; 80 mg/kg

2,2'-iminodiethanol (CAS: 111-42-2)

DNEL Workers - Inhalation; Long term local effects: 1 mg/m³

Workers - Dermal; Long term systemic effects: 0.13 mg/kg/day General population - Inhalation; Long term local effects: 0.25 mg/m³ General population - Dermal; Long term systemic effects: 0.07 mg/kg/day General population - Oral; Long term systemic effects: 0.06 mg/kg/day

PNEC - Fresh water; 0.02 mg/l

- marine water; 0.002 mg/l

- STP; 100 mg/l

Sediment (Freshwater); 0.092 mg/kgSediment (Marinewater); 0.009 mg/kg

Soil; 0.007 mg/kgOral; 1.04 mg/kg

Geraniol (CAS: 106-24-1)

DNEL Workers - Inhalation; Long term systemic effects: 161.6 mg/m³

Workers - Dermal; Long term systemic effects: 12.5 mg/kg/day

Workers - Dermal; Long term local effects: 11.8 mg/cm²

General population - Inhalation; Long term systemic effects: 47.8 mg/m³ General population - Dermal; Long term systemic effects: 7.5 mg/kg/day General population - Dermal; Long term local effects: 11.8 mg/cm² General population - Oral; Long term systemic effects: 13.75 mg/kg/day

ANTIQUAX MIRROR & GLASS CLEANER

PNEC - Fresh water; 0.011 mg/l

marine water; 0.001 mg/lIntermittent release; 0.108 mg/l

- STP; 0.7 mg/l

Sediment (Freshwater); 0.115 mg/kgSediment (Marinewater); 0.011 mg/kg

- Soil; 0.017 mg/kg

Linalool (CAS: 78-70-6)

DNEL Workers - Inhalation; Long term systemic effects: 2.8 mg/m³

Workers - Inhalation; Short term systemic effects: 16.5 mg/m³ Workers - Dermal; Long term systemic effects: 2.5 mg/kg/day Workers - Dermal; Short term systemic effects: 5 mg/kg/day Workers - Dermal; Long term local effects: 3 mg/cm²

Workers - Dermal; Short term local effects: 3 mg/cm²

General population - Inhalation; Long term systemic effects: 0.7 mg/m³ General population - Inhalation; Short term systemic effects: 4.1 mg/m³ General population - Dermal; Long term systemic effects: 1.25 mg/kg/day General population - Dermal; Short term systemic effects: 2.5 mg/kg/day General population - Dermal; Long term local effects: 1.5 mg/cm² General population - Dermal; Short term local effects: 1.5 mg/cm² General population - Oral; Long term systemic effects: 0.2 mg/kg/day General population - Oral; Short term systemic effects: 1.2 mg/kg/day

PNEC - Fresh water; 0.2 mg/l

- marine water; 0.02 mg/l

- STP; 10 mg/l

Sediment (Freshwater); 2.22 mg/kgSediment (Marinewater); 0.222 mg/kg

Soil; 0.327 mg/kgOral; 7.8 mg/kg

3-p-cumenyl-2-methylpropionaldehyde (CAS: 103-95-7)

DNEL Workers - Inhalation; Long term systemic effects: 5.83 mg/m³

Workers - Dermal; Long term systemic effects: 1.67 mg/kg/day

Workers - Dermal; Long term local effects: $7.43~\mu g/cm^2$

General population - Inhalation; Long term systemic effects: 1.45 mg/m³ General population - Dermal; Long term systemic effects: 0.83 mg/kg/day General population - Dermal; Long term local effects: 3.72 µg/cm² General population - Oral; Long term systemic effects: 0.83 mg/kg/day

PNEC - Fresh water; 1.09 μg/l

- marine water; 0.11 μg/l

- Intermittent release; 10.92 μg/l

- STP; 1 mg/l

Sediment (Freshwater); 0.126 mg/kgSediment (Marinewater); 0.013 mg/kg

- Soil; 0.025 mg/kg

A mixture of: (E)-oxacyclohexadec-12-en-2-one; (E)-oxacyclohexadec-13-en-2-one; a) (Z)-oxacyclohexadec-(13)-en-2-one and b) (Z)-oxacyclohexadec-(13)-en-2-one

ANTIQUAX MIRROR & GLASS CLEANER

PNEC - Fresh water; 2.7 μg/l

- marine water; 0.27 µg/l

- STP; 10 mg/l

Sediment (Freshwater); 21 mg/kgSediment (Marinewater); 4.2 mg/kg

- Soil; 5.44 mg/kg

Dodecanal (CAS: 112-54-9)

DNEL Workers - Inhalation; Long term systemic effects: 49.7 mg/m³

Workers - Dermal; Long term systemic effects: 14.1 mg/kg/day

Workers - Dermal; Long term local effects: 0.57 µg/cm²

General population - Inhalation; Long term systemic effects: 12.3 mg/m³ General population - Dermal; Long term systemic effects: 7 mg/kg/day General population - Dermal; Long term local effects: 0.28 µg/cm² General population - Oral; Long term systemic effects: 7 mg/kg/day

PNEC - Fresh water; 0.004 mg/l

- marine water; 0 mg/l

- Intermittent release; 0.035 mg/l

- STP; 10 mg/l

Sediment (Freshwater); 1.41 mg/kgSediment (Marinewater); 0.141 mg/kg

Soil; 0.278 mg/kgOral; 313 mg/kg

(S)-p-mentha-1,8-diene (CAS: 5989-54-8)

DNEL Workers - Inhalation; Long term systemic effects: 33.3 mg/m³

Workers - Dermal; Short term local effects: 0.222 mg/cm²

General population - Inhalation; Long term systemic effects: 8.33 mg/m³ General population - Dermal; Short term local effects: 0.111 mg/cm² General population - Oral; Long term systemic effects: 4.76 mg/kg/day

PNEC - Fresh water; 5.4 μg/l

marine water; 0.54 μg/lIntermittent release; 3.6 μg/l

- STP; 0.2 mg/l

Sediment (Freshwater); 1.322 mg/kgSediment (Marinewater); 0.132 mg/kg

Soil; 0.262 mg/kgOral; 133 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment that provides appropriate eye and face protection should be worn.

ANTIQUAX MIRROR & GLASS CLEANER

Hand protection To protect hands from chemicals, wear gloves that are proven to be impervious to the

chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon

as any deterioration is detected. Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-

marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use

should be used.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol. Clear liquid.

Odour Alcoholic.

Initial boiling point and range -40 - -2°C (LPG)

Flash point -104°C (LPG)

Upper/lower flammability or

explosive limits

1.4 - 10.9%(V)(LPG)

Vapour pressure 590 - 1760 KPa (LPG)

Auto-ignition temperature 365 °C / 689 °F (LPG)

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

The following materials may react strongly with the product: Oxidising agents.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised

container: may burst if heated Avoid heat, flames and other sources of ignition. Avoid the

following conditions: Freezing.

10.5. Incompatible materials

Materials to avoid No specific requirements are anticipated under normal conditions of use.

ANTIQUAX MIRROR & GLASS CLEANER

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Information given is based on data of the components. The blended product has not been

tested. No data is available for the mixture.

Acute toxicity - oral

ATE oral (mg/kg) 45,909.09

Acute toxicity - dermal

ATE dermal (mg/kg) 35,714.29

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 357.14

Inhalation Gas or vapour may irritate the respiratory system. May cause nausea, headache, dizziness

and intoxication. Vapour may irritate respiratory system/lungs.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Ingestion may

cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in mouth, oesophagus and stomach. May cause discomfort if swallowed. May

cause stomach pain or vomiting.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May cause eye irritation. May cause serious eye damage.

Route of exposure Inhalation Ingestion Skin and/or eye contact

SECTION 12: Ecological information

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability Volatile substances are degraded in the atmosphere within a few days. The other substances

in the product are not expected to be readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely. Exposure to aquatic environment unlikely.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces. The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

ANTIQUAX MIRROR & GLASS CLEANER

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and

its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste product or used

containers in accordance with local regulations

Do not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with

the requirements of the local Waste Disposal Authority.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

ANTIQUAX MIRROR & GLASS CLEANER

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC50: Lethal Concentration to 50 % of a test population.

LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC₅₀: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Aerosol = Aerosol

Key literature references and

sources for data

Source: European Chemicals Agency, http://echa.europa.eu/

ANTIQUAX MIRROR & GLASS CLEANER

Classification procedures Aerosol 1 - H222, H229: : Expert judgement.

according to SI 2019 No. 720

Revision date 23/03/2022

Revision 1

SDS number 5892

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.