



Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 2/16/2018 Revision date: 7/17/2023 Supersedes version of: 6/21/2022 Version: 13.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Rustins Strypit Paint & Varnish Stripper
UFI : R9RG-90AJ-P210-3107
Product code : STNF
Type of product : Solvents
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : Cleaning/washing agents and additives
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

Restrictions on use : Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Manufacturer

Rustins Ltd
Waterloo raod
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 - F +44 (0)208 452 2008
rustins@rustins.co.uk - rustins.ltd

Distributor

Excellence Ltd
43 Grange Parade,
Unit 43 Baldoyle Industrial Estate,
D13 Y860 Dublin
Ireland
T 00353 (0)1 8323300 - F 00353 (0)1 8323584
Orders@excellence.ie - www.excellence.ie

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16:30

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour.

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P280 - Wear eye protection, face protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9 EC-No.: 919-857-5 EC Index-No.: 649-327-00-6 REACH-no: 01-2119463258-33	$\geq 1 - < 5$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	$\geq 1 - < 5$	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	(3 ≤C < 10) STOT SE 2, H371 (10 ≤C ≤ 100) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Rustins Strypit Paint & Varnish Stripper	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methanol
IOEL TWA	260 mg/m ³
IOEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Alcool méthylique # Methanol
OEL TWA	266 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	333 mg/m ³
OEL STEL [ppm]	250 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Strypit Paint & Varnish Stripper	
Croatia - Occupational Exposure Limits	
Local name	Metanol
GVI (OEL TWA) [1]	260 mg/m ³
GVI (OEL TWA) [2]	200 ppm
Remark	Direktiva: 2006/15/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Metanol
BLV	24.7 mmol/mol Creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 7 mg/g creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/2018)
Cyprus - Occupational Exposure Limits	
Local name	Μεθανόλη
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	δέγμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
France - Occupational Exposure Limits	
Local name	Méthanol (alcool méthylique)
VME (OEL TWA)	260 mg/m ³
VME (OEL TWA) [ppm]	200 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Methanol
AGW (OEL TWA) [1]	130 mg/m ³
AGW (OEL TWA) [2]	100 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresortiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Strypit Paint & Varnish Stripper	
OEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Ireland - Occupational Exposure Limits	
Local name	Methanol [Methyl alcohol]
OEL TWA [1]	260 mg/m ³
OEL TWA [2]	200 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Metanolo
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Metanols (metilspirts, karbinols)
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Luxembourg - Occupational Exposure Limits	
Local name	Méthanol
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Portugal - Occupational Exposure Limits	
Local name	Metanol (Álcool metílico)
OEL TWA [ppm]	200 ppm
OEL STEL [ppm]	250 ppm

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Strypit Paint & Varnish Stripper	
Remark	P (Toxicidade percutânea); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Metanol/Alcool metilic
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool metilic
BLV	6 mg/l Indicator biologic: Metanol - Material biologic: urină - Momentul recoltării: sfârșit de schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Serbia - Occupational Exposure Limits	
Local name	метанол
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	EУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovenia - Occupational Exposure Limits	
Local name	metanol (metilalkohol)
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	1040 mg/m ³
OEL STEL [ppm]	800 ppm
Remark	K (Lastnost lažjega prehanjanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	metanol
BLV	15 mg/l Parameter: metanol - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene, pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikih
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Metanol (Alcohol metílico)
VLA-ED (OEL TWA) [1]	266 mg/m ³
VLA-ED (OEL TWA) [2]	200 ppm

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Strypit Paint & Varnish Stripper	
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Spain - Biological limit values	
Local name	Metanol (Alcohol metílico)
BLV	15 mg/l Parámetro: Metanol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
North Macedonia - Occupational Exposure Limits	
Local name	метанол (метилалкохол)
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	(К) својство на полесно пренесување на супстанците во организмот преку кожата; (BAT) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves.

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Characteristic odour.
Odour threshold	: Not available
Melting point	: No data available.
Freezing point	: Not available
Boiling point	: > 35 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 3 °C
Auto-ignition temperature	: No data available.
Decomposition temperature	: Not available
pH	: 7
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.98
Relative vapour density at 20°C	: No data available.
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
	pH: 7

methanol (67-56-1)	
pH	NO DATA AVAILABLE
Serious eye damage/irritation	: Not classified
	pH: 7

methanol (67-56-1)	
pH	NO DATA AVAILABLE
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.

methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified
Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT / PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport document description				
UN 1263 PAINT / PAINT RELATED MATERIAL, 3, II, (D/E)	UN 1263 PAINT RELATED MATERIAL, 3, II	UN 1263 Paint related material, 3, II	UN 1263 PAINT RELATED MATERIAL, 3, II	UN 1263 PAINT RELATED MATERIAL, 3, II

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640C, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: L1.5BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E2
--------------------------------	------

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640C, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640C, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

Organic solvent : Yes

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Asp. Tox. 1	Aspiration hazard, Category 1

Rustins Strypit Paint & Varnish Stripper

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.