



TECHNICAL DATA SHEET

Antiquax Liquid Floor Wax Polish

www.antiquax.co.uk

Waterloo Road, London NW2 7TX
Telephone: +44(0)20 8450 4666

LFW500 and LFW1

Type	A premium liquid wax polish designed to impart high levels of shine and foot traffic protection primarily to timber floors
Intended Use	For use on all types of wood flooring and panelling, particularly sealed or lacquered wood. Do not use where increased slip would create hazards, i.e. wet floors etc. This product is not a non-slip polish.
Special Features	Deep lasting shine. Resists marking and black heel scuffing. Silicone free. Ideal for parquet flooring. May be treated with low speed mechanical buffing equipment to provide enhanced gloss.
Preparation	The surface must be clean, dry and free of dirt, grease and other contaminants.
Application	Shake the container thoroughly. Apply sparingly to a clean, dry, soft cloth and work along the grain of the wood and into the joints, avoiding excessive wetting. Allow to dry, then buff lightly with a clean dry soft cloth.
Coats	One application should be sufficient.
Drying Time	Quick drying
Re-coating Time	Re-apply as required
Application Temp.	Ideally 15-25°C
Coverage	Approximately 60 square metres per litre depending on the condition and porosity of the wood.
Maintenance	Re-apply as required.
Compatibility	Compatible with all types of wood flooring etc. Unsuitable where increased slip is a hazard.
Settlement	Shake well before use.
Shelf-life/Storage	A very long time if stored in original sealed container in a cool dry place.
Hazards	Flammable. Keep away from children. Keep container tightly closed. Keep away from all sources of ignition. No smoking. A full Health & Safety Data Sheet is available on request or on www.antiquax.co.uk
Clean-Up	Hands and application cloths can be cleaned in warm soapy water
Sizes	500 ml and 1 litre cans

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.