

FINISHING WAX POLISH - LIGHT / MEDIUM TO DARK

PRODUCT DESCRIPTION

Priory Polishes Finishing Bees Wax Furniture Polish, comes in two options, Light Tones or Medium to Dark Tones. Our quality blended Beeswax is ideal for all shades of wood as it feeds, nourishes and protects your finish and will enhance the sheen. This has been specially developed from a traditional recipe and is most suitable for previously finished or sealed interior woods.

DIRECTIONS: For best results, we recommend cleaning the surface first using Priory Polish Reviver on furniture or Priory Polishes Clock Case Restorer on clocks using very fine wire wool, this will remove the dirt & grease ready for treatment of the wax finish.

Once you have revived your wood finish, take a clean cotton or a brush in hand to reach areas, and apply small amounts of wax evenly in the direction of the wood grain where possible. Lightly remove any excess and then leave to dry for around 10 minutes. Once dry, buff off until the desired sheen has been reached with a soft dry cloth. Several applications can be applied to deepen the colour and enhance the required finish.

IMPORTANT: Always test products first on a spare surface or inconspicuous area to check colour, compatibility and end result.

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name: Finishing Bees Wax Furniture Polish / Finishing Wax Polish
Composition / Ingredients: Turpentine, Wax

1.2 Relevant identified uses of the substance or mixture and uses advised against
No specific uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Company Name :	Priory Polishes
Address:	Unit 6, Deanfield Drive,

	Link 59 Business Park, Clitheroe, Lancashire. BB7 1QJ
Website:	www.priorypolishes.co.uk
Tel:	01200 425443
Email:	info@priorypolishes.co.uk

SECTION 2 : HAZARDS IDENTIFICATION

2.1 Classifications of the substance or mixture

Classification under CLP : Regulation (EC) No.1272/2008

Physical Hazards

Flammable Liquid 3 - H226

Health Hazards

Skin Irritant 2 - H315

Eye Irritant 2 - H319

Skin Sensitivity 1 - H317

STOT SE 2 - H336

Asp. Toxic 1 - H304

Environmental Hazards

Chronic aquatic toxicity 3 - H412

Classification according to EU Directives 67/548/EEC or 1999/45/EC

For the full text of the R-phrases and H-statements mentioned in this Section, see Section 16

2.2 Label elements



Signal Word : **DANGER**

Hazard Statements

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P210:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280:	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378:	In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P403+P235:	Store in a well-ventilated place. Keep cool.
P501:	Dispose of contents/ container in accordance with national regulations.
P261:	Avoid breathing vapour/ spray.
P264:	Wash contaminated skin thoroughly after handling.
P271:	Use in a well-ventilated area or only outdoors.
P272:	Contaminated work clothing should not be allowed out of the workplace.
P273:	Avoid release to the environment.
P405:	Store locked up.

2.3 Other hazards

PBT : This product is not identified as a PBT substance

SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

HYDROCARBONS, C9- 11, N-ALKANES, CYLICS

3 - H226; Flam. Liq.
 3 - H336; STOT SE
 1 - H304; Asp. Tox.
 3 - H226; Flam. Liq.
 4 - H302; Acute Tox.
 4 - H312; Acute Tox.
 4 - H332; Acute Tox.
 2 - H315; Skin Irrit.

TURPENTINE OIL

2 - H319; Eye Irrit.
 1 - H317; Skin Sens.
 1 - H304; Asp. Tox.
 2 - H411; Aquatic Chronic

For the full text of the R-Phrases and H-Statements mentioned in this section, see section 16

SECTION 4 : FIRST AID MEASURES

4.1 Description of first aid measures

General Advice :	Take off all contaminated clothing immediately. Wash immediately with plenty of soap and water.
Skin Contact :	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Eye Contact :	Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes
Ingestion :	Call a physician immediately. Clean mouth with water.
Inhalation :	Remove from exposure, lie down. Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Immediate medical attention is required.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact. May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.

Eye contact. Irritating to eyes.4.3 Indication of any immediate medical attention and special treatment needed.

Ingestion. May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Inhalation. A single exposure may cause the following adverse effects: Headache. Nausea, vomiting, Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Delayed / immediate effects. Immediate effects can be expected after short-term exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician : Treat symptomatically

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Water spray. Carbon dioxide (CO₂) Dry chemical. Chemical Foam. Cool closed containers exposed to fire with water spray.

5.2 Special hazards arising from the substance or mixture

Combustible material. Flammable. Containers may explode when heated. Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for fire-fighters

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

In the event of fire, wear self-contained breathing apparatus pressure-demand, (SCBA) MSHA/NIOSH (approved and equivalent) and full protective gear conforming to European standard EN469 will provide a basic level of protection for chemical incidents. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges. For personal protection see Section 8. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities. If material reaches soil inform authorities responsible for such cases.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Remove all sources of ignition if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4 Reference to other sections

Reference to other sections : Refer to section 8 and 13

SECTION 7 : HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on Safe Handling: Keep container tightly closed. Handle and open container with care. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Use respirator with appropriate filter if vapours or aerosol are released. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity.

Hygiene Measures: Keep away from food, drink and animal feeding stuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday Take off all contaminated clothing immediately. Provide adequate ventilation. Avoid contact with the skin and the eyes. Do not breathe gas/fumes/vapour/spray.

7.2 Conditions for safe storage, including any incapacibilities

Keep in a dry, cool and well ventilated place, away from incompatible materials (see Section 10). Store locked up & keep away from oxidising materials, heat and flames.

Storage: Keep tightly closed in a dry and cool place. Protect against light. Protect from Contamination. Keep in a well-ventilated place. Keep away from food, drink and animal feeding stuffs.

Storage class Flammable liquid storage

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.

SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Turpentine, Oil	WEL 100 ppm 566 mg/m ³	Long-term exposure limit (8hr TWA)
-----------------	-----------------------------------	------------------------------------

WEL 150 ppm 850 mg/m³ Short-term exposure limit
(15-min)

WEL = Workplace Exposure Limit

8.2 Exposure controls up to HERE

Engineering Measures: Refer to protective measures listed in sections 7 & 8.

Hand Protection: Wear suitable gloves. The glove material has to be impermeable and resistant to the product and should be replaced at first signs of wear. Nitrile rubber, Neoprene, Natural rubber, PVC (see manufacturers recommendations for breakthrough time).

Skin & Body Protection: Wear appropriate protective gloves and clothing to prevent skin exposure.

Eye Protection: Tightly fitting safety goggles.

Respiratory Protection: When workers are facing concentrations above the exposure limit, they must use appropriate certified respirators. To protect the wearer, respiratory equipment must be the correct fit and be used and maintained properly.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice.

Environmental Controls: Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical State :	Coloured paste
Appearance :	Clear or Dark Brown
Odour :	Aromatic
pH :	Not applicable
Solubility in water :	Insoluble in water. Immiscible with water
Melting point oC :	+50°C
Flash Point :	43°C Not specified.
Viscosity :	Kinematic viscosity > 20.5 mm ² /s

9.2 Other Information

SECTION 10 : STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity: Stable under recommended storage conditions.

10.2 Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3 Possibility of hazardous reactions

The following materials may react strongly with the product: Oxidising agents.

10.4 Conditions to avoid

Exposure to air. Incompatible products. Heat Impurities. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents. Acids.

10.6 Hazardous decomposition products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product Information

Oral:	5,000.0
Dermal :	11,000.0
Inhalation :	110.0
Skin Irritation :	Irritating
Eye Damage :	Causes serious eye irritation
Respiratory :	No data available
Carcinogenicity :	No data available. (There are no carcinogenic chemicals in this product).
STOT – single exposure :	STOT SE 3 - H336 May cause drowsiness or dizziness.

Other relevant toxicity information :

Symptoms / effects both acute and delayed : May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation. Aspiration hazard if swallowed, Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness,

disorientation, vertigo. Narcotic effect. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

SECTION 12 : ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity effects : Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

The degradability of the product is not known.

12.3 Bio accumulative potential

No data available on bioaccumulation.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

The PBT or cPvB criteria of Annix XIII to the REACH Regulation does not apply to inorganic substances.

12.6 Other adverse effects

Harmful effects to aquatic organisms. Do not flush into surface water or sanitary sewer system.

SECTION 13 : DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not let product enter drains.

N.B : The user attention is drawn to the existence of regional or national regulations regarding disposal.

SECTION 14 : TRANSPORT INFORMATION

UN Number :	UN 1263
UN Proper Shipping Name :	PAINT RELATED MATERIAL
Transport Hazard Class(es) :	3
Packing Group :	III
Environmental Hazards :	Dangerous for the environment. Product is a marine pollutant according to the criteria set by IMDG/IMO

SECTION 15 : REGULATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture:

The regulatory information given above only indicates their principal regulations specifically applicable to the product described in the safety data sheet. The users attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

5.2 Chemical Safety Assessment

Chemical Safety Assessment : A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16 : OTHER INFORMATION

Full text of H-Statements used in S2 & S3

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Legal Disclaimer : The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Revision Date20/05/21