



## Lubricating Wax

- Lubricates tools and machinery
- Keeps working parts moving freely
- Helps reduce resin build-up from softwood
- Reduces corrosion on all bare metal surfaces
- Silicone free



### USAGE

Interior

### COVERAGE

1 L  
10-12 m<sup>2</sup>

### APPLICATION

Brush or  
Cotton Cloth

### DRYING TIME

Minimum 10  
minutes

### TOOL CLEANING

White Spirit

### Product use

Liberon Lubricating Wax is specially formulated to lubricate and clean saw blades, cutter blades, machine table, lathes, planers, veneer presses and G-clamps to increase efficiency and longevity.

Its special properties will inhibit the formation of rust and assist in the quick cleaning and easy removal of glue from veneer presses and G-clamps.

### Preparation

Shake well before use. Ensure the surface is clean, dry and free from rust. Remove rust using Liberon Rust Remover.

### Application

Apply a thin coat of Lubricating Wax using a brush or clean cotton cloth. Allow to dry before use. Re-apply as required.

**Important:** Ensure all working machinery is switched off and stationary before using Liberon Lubricating Wax. Allow to dry before switching equipment on.

### Maintenance

Use as required to keep tools and machinery in good condition.

### Packaging

Lubricating Wax is available in 500 ml and 1 L containers.

### Health and Safety

Harmful. Contains aliphatic solvents. Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed do not induce vomiting: seek medical advice immediately and show this container or label.