

PRODUCT DATA SHEET

Product	Interior & Exterior Wood Filler
Type	A paste based on fillers, pigments and binder. Available in pine, light, natural, medium and dark oak, light, medium and dark mahogany, light walnut, teak, ebony, beech, maple, black and white shades.
Intended Use	To fill nail holes, dents and cracks in wood. For interior and exterior use, unless suitably over-coated.
Special Features	Does not crack. Can be drilled or sanded like wood. Takes stains if mixed before applying. May shrink when filling large holes, therefore build up with two or more applications
Preparation	Wood should be sanded smooth, clean and free from wax. If wood is to be painted, it should be primed before Brummer Wood Filler is applied. For clear varnish finishes, apply the correct colour. Brummer Wood Filler to the bare wood. Artist's acrylic colours may be added to Brummer Wood Filler to match it to the natural wood.
Application	Apply using a putty knife, forcing into the cracks and holes. Leave slightly proud of the surface to allow for possible shrinkage. Sand off any excess. Brummer Wood Filler is supplied ready for use, but if it becomes hard, adding a little water may soften it. Allow to dry for about 1 hour, depending on temperature, then sand smooth. If the hole to be filled is quite deep, it may be filled in stages to minimise shrinkage. Deeper holes will need extended drying periods. If applying a clear finish, Brummer Wood Filler can be disguised by painting a pattern onto the dry filler with artists' acrylic colours before varnishing.
Coats	N/A
Drying Time	30 minutes – 1 hour depending on the temperature and humidity
Re-coating Time	Leave to dry for 1 hour before applying undercoat or varnish. Deep filled area will require longer drying times.
Application Temp.	Ideally 15-25°C.
Coverage	N/A
Maintenance	N/A
Compatibility	Can be used under many paints and varnishes. Most brands should be compatible but if in doubt carry out a small test.
Settlement	N/A
Shelf-life/Storage	A very long time if stored in original sealed container in a cool dry place
Hazards	Low-hazard. A full Health Safety Data Sheet is available upon request or visit www.rustins.co.uk
Clean-Up	Clean equipment with water whilst soft.
Sizes	250g